


Architectural Doors

LD9000 MINERAL CORE

APPLICATIONS & BENEFITS

Recommended for Architectural applications that require a ninety-minute fire-rated door. Available in a wide variety of hardwood, hardboard and plastic laminate faces.



LD Lynden Door™

LYNDEN DOOR, INC.
P.O. BOX 528
177 WEST MAIN ST.
LYNDEN, WA 98264
PHONE (360) 354-5676
FAX (360) 354-3738

SPECIFICATIONS

MAXIMUM SIZE

Single doors 4'0" x 10'0"
Maximum size door/transom 4'0" x 10'0"
Paired Doors: Dependent on blocking and hardware preps. 8'0" x 9'0"
Call Lynden Door, Inc. for further information.

DOOR THICKNESS

1³/₄" standard.

STILES

Firestop II with solid hardwood edges matching (compatible with) the face veneer. Maximum 1/4" wood, minimum 1" composition (after trim).

RAILS

Firestop II composite rails with outer band of softwood. Top rail: Maximum 1/4" optional wood outerband, minimum 1" composition (after trim). Bottom rail: Minimum 1" composition, no wood allowed. Matching (compatible) top rail is available.

BONDED CORE AND FRAME ASSEMBLY

Georgia Pacific ninety-minute mineral core with the stiles bonded to the core and the stiles and rails bonded together.

FACES

Pregraded: Hardboard, Medium Density Overlay, Premium 3-ply veneered skins (minimum 1/50" veneer before sanding), or Plastic Laminate (overlaid on a sanded hardboard substrate). Veneers available in a wide variety of species and cuts.

ADHESIVES

Core and frame assembly and veneer application all with Type 1, waterproof adhesives.

BLOCKING

Special inner blocking options may be specified for reinforcing of hardware, including lockblocks.

FACTORY MACHINING/DETAILING

Complete range of machining capabilities and detailing available. Rated doors must be in accordance with Warnock Hersey International, Inc. and National Fire Protection Association Standards (NFPA 80, latest edition). Lynden Door, Inc. recommends factory prefitting on all fire doors.

LIGHT OPENINGS

For ninety-minute rated doors, the total visible area of single or multiple lights may not exceed 100 sq. in. per leaf, with a maximum width of 10", or a maximum height of 33". All cut-outs must be 6" from the edge of the door or any other cutouts and/or hardware preps, with a minimum bottom rail of 10".

WARRANTY

The life of the original installation for interior use only. See warranty terms and conditions. Use of Lynden Door, Inc. LD9000 doors in exterior applications is neither recommended nor warranted.

NOTE

All Lynden Door, Inc. doors meet or exceed W.D.M.A.I.S.1A standards.