



CROSSMORE™

Molded Panel Hollow Core

Residential, Standard, Light Commercial, 6'8" / 7'0"



Craftsman Collection

By Lynden Door
Authentic, by Design

The Crossmore™ door leads off the new Craftsman Collection by Lynden Door. Faithful to the Craftsman movement, the Crossmore's flat, recessed panel is *authentic, by design*.



Lynden Door Inc. is third-party Chain of Custody certified by the Forest Stewardship Council (FSC) and Sustainable Forestry Initiative (SFI).

GreenDor™ is a collection of Lynden Door product options that support green building. GreenDor™ attributes are applicable to LEED for Homes, the National Green Building Standard™, Regreen and North American home builder association programs such as Built Green™.



CROSSMORE™

- Authentic recessed flat panel design
- Clean, Shaker-influenced profile is at home in Craftsman architecture or contemporary spaces
- Primed — optional Factory Finishing
- Smooth finish

CROSSMORE™ 6'8" / 7'0" 7'0" doors are available by special order only.

1 3/8"
PASSAGE

1'6"	1'8"	1'10"	2'0"	2'2"	2'4"	2'6"	2'8"	2'10"	3'0"
		●							

NOTE: Lock block placement engineered for cylindrical lock with bore holes at 40" and 44" down from top of door.

- This model does not contain sufficient backset space for standard cylindrical lock sets. Contact your local Lynden Door representative for more information.

1 3/8"
BIFOLD

2'0"	2'6"	2'8"	3'0"	4'0"	5'0"	5'4"	6'0"
		*					

NOTE: Bifolds are 6'7" tall or optionally 6'11". Both interior and exterior faces are matching molded panels. 4'0" and wider are 4-unit configurations.

- * Check with your Lynden Door representative for availability.

Molded doors have become a major force in the residential and light commercial built environment. Why?

Design Forward

Add style, elegance and decorating consistency to your projects. Rediscover doors as an integral part of interior design.

Stable Performance

No cracking or panel separation due to seasonal humidity changes.

Environmentally Intelligent

No old growth timber is harvested for the manufacture of molded panel door skins. Instead, by-products from sawmill operations (within 100 miles of the manufacturing facility) are collected and used to produce molded panels. Molded panels are a composite produced by mixing — and then compressing — wood fiber and a resinous binder. The fibrous materials are 50% pre-consumer recycled wood waste, by weight. The complete door slab is conservatively estimated to be 35% recycled content, by weight. The binder contains no added urea-formaldehyde. Contact your Lynden Door representative for the full range of GreenDor™ attributes that may be applied to Crossmore doors.

Superior Value

Compelling design and customization opportunity at a significant value versus solid wood doors.



Printed on FSC-certified paper

Dealer information:

