


Lynden Door
Commercial Series
GREENDOR™
CD200 FSC® NAUF HPDL 5 Ply
Particleboard Core
FSC® CoC-NAUF
Non Rated or 20 min.


FACES:	High pressure decorative laminate (HPDL) faces to meet minimum requirements of National Electrical Manufacturers Association (NEMA) Standard LD 3 High Pressure Decorative Laminates. Note: <i>Not all HPDL can be used in this product, contact factory for details.</i>	
SUBSTRATE:	Engineered wood composites	
CORE:	Particleboard ANSI A208.1 LD1	Option: LD2
STILES:	Softwood, fire rated composite with decorative laminate face, AWS Type-C-HPDL Option: Wood edges painted or stained to complement decorative laminate face	
RAILS:	Mill option structural composite lumber, wood or composite material.	
ASSEMBLY:	Stiles and rails are securely bonded to the core and the assembled unit is sanded prior to application of faces.	
ADHESIVES:	Type 1	
MAXIMUM SIZE:	POSITIVE PRESSURE WITH HOSE STREAM 4'0" x 9'0" (1220mm x 2743mm)	NEUTRAL PRESSURE WITH HOSE STREAM 4'0 x 10'0 (1220mm x 3050mm)
THICKNESS:	20 min rated 1 3/4" (45 mm) Non-rated 1 3/8" (35 mm) or 1 3/4" (45 mm)	Option: Up to 2 1/2" (63.5 mm) Option: Up to 2 1/2" (63.5 mm)

WARRANTY:	5 years, for interior use only. See warranty terms and conditions	
STANDARDS:	Performance attributes meet or exceed WDMA IS-1A and AWS Extra Heavy Duty Standards when specified with blocking for surface applied hardware without through bolts. Option: WDMA IS-1A and AWS Custom Grade	
FIRE RATING:	Positive Pressure Category B or Neutral Pressure Option: Positive Pressure Category A Neutral Pressure with hose stream tested in accordance with UBC-7 1994 and UL-10B Positive Pressure tested in accordance with UBC 7-2 1997, UL-10C and NFPA 252 For additional information on fire doors please refer to the Lynden Door Fire Door Technical Sheets.	
ACOUSTICAL RATING	STC 32 ASTM E90-09 – Non Operable*	OITC 30 ASTM E90-09 – Non Operable
ENVIRONMENTAL Attributes:	* When installed with two rows of Pemko S773, one row of Pemko S44, a Pemko PDB411AE Auto Door Bottom, and Pemko ACP112 Corner pads the STC performance will be equal to an operable test rating of STC 32 This product is an FSC® Mixed Source product with all the wood in the door being FSC® Certified or FSC® Controlled. All adhesives and binders in this product contain no added urea-formaldehyde. This product is manufactured with pre-consumer recycled material. This product may contribute to credits requiring regional harvesting or recovery of raw material and regional manufacturing. For additional information on product contribution please refer to the GREENDOR™ Contribution Sheets.	

Manufacturing Options

BLOCKING:	Special blocking options may be specified. (Reference WDMA I.S.1A blocking options HB-1 through HB-8)
MACHINING:	Machining for hardware, open cutouts, installation of lifes and louvers, applied moldings, plant ons, raceways, concealed vertical rods, decorative routing, dutch doors, doors and transoms - Hardware cutouts shall be factory machined from manufacturers' templates and shop drawings.