


**Lynden Door
Architectural Series**
**LDSD38 SR-5
Acoustical Composite Core**
Non Rated


FACES:	HPVA Architectural "A" grade wood veneer (minimum thickness 1/50" before sanding) Options: "AA" grade wood veneer, paint grade MDO Hardboard (PC3)
SUBSTRATE:	Engineered wood composites
CORE:	Proprietary acoustical material
STILES:	(CE) Compatible with face veneer, mill option AWS Type A wood or Type B veneered Option: (ME) Matching with face veneer
RAILS:	Mill option structural composite lumber, wood or composite material.
ASSEMBLY:	Stiles and rails are securely bonded to the core and the assembled unit is sanded prior to application of faces.
ADHESIVES:	Type 1
MAXIMUM SIZE:	4'0" x 8'0" (1220mm x 2438mm)
THICKNESS:	1 3/4" (45 mm)

WARRANTY:	Life of original installation for interior use only. See warranty terms and conditions	
STANDARDS:	WDMA IS-1A and AWS Custom Grade	Option: WDMA IS-1A and AWS Premium Grade
	Performance attributes meet or exceed WDMA IS-1A and AWS Extra Heavy Duty standards when specified with blocking for surface applied hardware without through bolts.	
FIRE RATING:	Non-Rated	
ACOUSTICAL RATING	STC 38 ASTM E90-09 – Non Operable	OITC 34 ASTM E90-09 – Non Operable
ENVIRONMENTAL Attributes:	Recycled content, regionally recovered and manufactured may apply – see GREENDOR™ Contribution Sheets.	

Manufacturing Options

BLOCKING:	Special blocking options may be specified. (Reference WDMA I.S.1A blocking options HB-1 through HB-8). Additional blocking may affect STC rating	
MACHINING:	Machining for hardware, open cutouts, installation of lites and louvers, applied moldings, plant ons, raceways. - Hardware cutouts shall be factory machined from manufacturers' templates and shop drawings. Note: Lite and louver cutouts have not been tested and will affect STC ratings, contact factory prior to attempting any lite cutouts.	
TRANSPARENT FINISH	WDMA TR6 / AWS System 9 -UV cured catalyzed polyurethane finishes in standard and custom match stains	Options: Other finish systems available
OPAQUE FINISH:	Factory painting in standard and custom match colors	Options: Standard or color tinted priming available