

**Lynden Door
Standard Series****SD10SS
Semi-Solid Core****Non Rated**

FACES:	Hardwood Veneers, Prefinished Flush Hardboard, Prefinished Embossed Hardboard, Primed Flush Hardboard, Primed Embossed Hardboard
CORE:	Kraft corrugated paper
STILES:	Mill Option Solid Softwood, FJ Softwood, MDF Option: (CE) Compatible with face veneer
RAILS:	Mill option MDF, composite material, or wood.
ASSEMBLY:	Non Bonded (Loose Lay).
ADHESIVES:	Type 2
MAXIMUM SIZE:	4'0" x 8'0" (1220mm x 2438mm)
THICKNESS:	1 3/8" (35 mm) or 1 1/4" (45 mm)
WARRANTY:	1 year, for interior use only. See warranty terms and conditions. Possible extended warranties available, contact factory for options.
STANDARDS:	Performance attributes meet or exceed WDMA IS-1A and AWS Standard Duty standards when specified with blocking for surface applied hardware without through bolts
FIRE RATING:	Not applicable
ACOUSTICAL RATING	Not applicable
ENVIRONMENTAL Attributes:	Recycled content, regionally recovered and manufactured, may apply – see GREENDOR™ Contribution Sheets.

Manufacturing Options

BLOCKING:	4" stile, 4" top rail and 8" bottom rail particleboard blocking. Special blocking options may be specified.
MACHINING: cutouts	Machining for hardware, open cutouts, installation of lites and louvers, dutch doors, doors and transoms - Hardware shall be factory machined from manufacturers' templates and shop drawings.
TRANSPARENT FINISH	WDMA TR6 / AWS System 9 -UV cured catalyzed polyurethane finishes in standard and custom match stains Options: Other finish systems available
OPAQUE FINISH:	Factory painting in standard and custom match colors Options: Standard or color tinted priming available