

	MULTI-FAMILY RESIDENTIAL											
	HOLLOW CORE (H8/H4)		PARTICLE CORE (P20)		SCL CORE		FIRE CORE					
	SD10	LD1000	SD20	LD2000	SD35	LD3500	SD45	LD4500	SD60	LD6000	SD90	LD9000
DOOR OPENINGS												
Unity Entry			*	*	*	*	*	*				
Room Interior	*	*	*	*								
Common Areas			*	*	*	*	*	*	*	*	*	*
Stairwells			*	*	*	*	*	*	*	*	*	*
Service Areas			*	*	*	*	*	*	*	*	*	*
ATTRIBUTES												
WDMA Performance Rating												
Extra-Heavy Duty		* 3		* 3		* 3		* 3		* 3		* 3
Heavy Duty												
Standard Duty	* 3		* 3		* 3		* 3		* 3		* 3	
Life & Safety												
(Positive or Neutral Pressure) Fire Rating			20 MIN	20 MIN	20 MIN	20 MIN	45 MIN	45 MIN	60 MIN	60 MIN	90 MIN	90 MIN
STC Acoustic Rating			STC 33	STC 32		STC 35					STC 32	STC 32
Door Face Options												
High Pressure Decorative Laminate		*		*		*		*		*		*
Wood Veneer	*	*	*	*	*	*	*	*	*	*	*	*
Primed Medium Density Overlay		*		*		*		*		*		*
Primed MDF/HDF	*	*	*	*	*	*	*	*	*	*	*	*
Primed Molded Panel	*		*		*		*		*		*	
Wet Finish MDF	*		*		*		*		*		*	
Vertical Edge Options												
Hardwood	2	1	2	1	2	1	2	1	2	1	2	1
Laminate				2		2		2		2		2
Veneer		2		2		2		2		2		2
Softwood	1		1		1		1		1		1	
Finger-joint	2		2		2		2		2		2	
MDF	1		1		1		1		1		1	
Environmental Preferred Options												
Rapidly Renewable								LD45AG				
No Added Urea-Formaldehyde	*	*	*	*	*	*	*	*	*	*	*	*
FSC® Certified CoC				*		*		LD45AG				
Recycled Material	*	*	*	*	*	*	*	*	*	*	*	*
Warranty												
Lifetime		*		*		*		*		*		*
One year	*		*		*		*		*		*	

Key
* - Available
1 - Typical Product Offering
2 - Optional Product Offering
LD45AG - Only available in a single swing application up to a 4'0 x 8'0 opening size.
* 3 - Optional blocking is required when surface applied hardware is mounted with wood screws in lieu of thru bolts.
20, 45, 60 & 90 MIN - Rated in Neutral & Positive Pressure (as required by local code)